For 3 Way control of hot water or chilled water up to 50%Glycol & 15 PSI saturated steam.







Description

The Industrial Ball Valve Series are actuated Ball Valves that provide digital or analog control of hot water, chilled water containing up to 50% glycol or 15 PSI steam. Each unit is comprised of a rotary actuator and linkage assembly coupled to the valve body that offers, high pressure differential Close-Off.

Valve sizes range from 1/2 inch to 2 inches with a maximum valve body rating of 400 PSIG for a 3 way. These low profile, compact units can be installed with ease in the often tight, restricted areas found in unit ventilators, fan coils, terminal reheat coils and larger air handlers.




FIG. I PRESSURE vs. TEMPERATURE

Specifications

Valve Flow Type: 3 Way: Modified Linear

Service: Hot water, chilled water, glycol up to 50%, 15 PSIG, saturated

steam. (Optional: 150 PSIG saturated steam)

Static Pressure & Temperature: (Refer to Fig. I)

Maximum Working Pressure: 3 Way: 400 PSIG WOG

Body: Bronze

Ball & Stem: Stainless Steel

Stem Seals: Composite of reinforced Teflon & EPDM "O" rings


Seats: Reinforced Teflon

End Connections: Standard NPT Female

DIMENSIONS - INDUSTRIAL BALL VALVES neptronic 1/2"- 3/4" BT/BM ACTUATOR VALVE ASSEMBLY



BT/BM Actuated Valve Assembly






SIZE	Cv	Kv	VALVE MODEL PREFIX	CLOSE OFF PSI	A	В	O	D	Е
1/2"	5	4	ST A0048XS1	100	2.25	1.09	3.20	6.45	1.18
3/4"	12	10	ST B0120XS1	100	3.00	1.50	3.60	6.85	1.62

^{*} All dimensions are in Inches.

DIMENSIONS - INDUSTRIAL BALL VALVES 1"- 1-1/2" TT/TM ACTUATOR VALVE ASSEMBLY neptronic*



TT/TM Actuated Valve Assembly






SIZE	Cv	Kv	VALVE MODEL PREFIX	CLOSE OFF PSI	Α	В	С	D	E
1"	14	12	ST C0140XS1	300	3.18	1.59	4.00	7.75	1.71
1-1/4"	21	18	ST D0210XS1	300	3.95	1.97	4.30	8.05	2.01
1-1/2"	34	29	ST E0340XS1	150	4.40	2.21	4.70	8.45	2.38

^{*} All dimensions are in Inches.



RT/RM Actuated Valve Assembly





SIZE	Cv	Kv	VALVE MODEL PREFIX	CLOSE OFF PSI	Α	В	С	D	E
2"	47	40	ST F0470XS1	75	4.69	2.34	5.00	8.75	2.50

^{*} All dimensions are in Inches.