

Output and Consumption

Model	Capacity	Power (kW)	Amperage			Width	Height	Depth	Height with SDU
			120V	208V	240V				
SKR14	4.5 lb/hr 2.0 kg/hr	1.4	12A	-	-	10.5" 267mm	14.5" 368mm	9" 229mm	19.75" 500mm
SKR25	7.5 lb/hr 3.4 kg/hr	2.5	-	12A	11A	10.5" 267mm	14.5" 368mm	9" 229mm	19.75" 500mm
SKR30	9 lb/hr 4.1 kg/hr	3	-	14.5A	13A	10.5" 267mm	14.5" 368mm	9" 229mm	19.75" 500mm
SKR40	12 lb/hr 5.4 kg/hr	4	-	19.2A	17A	10.5" 267mm	14.5" 368mm	9" 229mm	19.75" 500mm

Note: Operation with maximum 0.5" (125Pa) duct static pressure at steam distribution manifold location.

Output and Consumption

Model	Capacity	Power	Voltage	Amperage	Width	Height	Depth	Height with SDU
VILLA SKR3E	3 kg/hr	2.3 kW	230 Vac/1 ph	10 A	267 mm	368 mm	229 mm	500 mm
CHATEAU SKR4E	3.75 kg/hr	2.8 kW	230 Vac/1 ph	12.2 A	267 mm	368 mm	229 mm	500 mm
BELVEDERE SKR5E	5 kg/hr	3.7 kW	230 Vac/1 ph	16.1 A	267 mm	368 mm	229 mm	500 mm

Note: Operation with maximum 125Pa duct static pressure at steam distribution manifold location