

SKG4-Gas Fired Humidifier Brochure



neptronic®

SKG4-Gas Fired Humidifier Brochure

The SKG4 gas fired humidifier generates mineral free, odorless, sterile steam by using the power of natural gas or propane. Cost of operation and its carbon footprint is much lower than electric humidifiers with equivalent control accuracy.

Advantages

- Steam capacity from 110 to 810lbs/hr (50 to 370kg/hr)
- Functions with Tap, RO or DI water
- Combustion efficiency: 83% to 87%
- Easy servicing: clean and re-install within minutes
- Self-adjusting burner for altitude compensation
- Waste water drained below 140°F (60°C)
- Smallest footprint in the industry
- Anti-Foaming Energy Conservation (AFEC) System
- Advanced controller with multiple connectivity options

Typical Applications

When natural gas or propane or LPG is available on site, the SKG4 gas fired humidifier is ideal for capacities from 110-810lb/hr (50-370kg/hr). Typical applications for SKG4 humidifiers include:

Hospitals/Institutions



Paint Booths



Clean Rooms



Laboratories




Commercial




Typical Installation

The SKG4 gas fired humidifier is designed to distribute steam into a duct or AHU. Common water supply inlet, gas supply inlet, drain outlets and flue outlet can be located either on the right or left hand side of the SKG4. Steam outlets are located on top of each module. Air inlet can be through the front door with natural ventilation or from top of each module if direct combustion air (sealed combustion) option is selected.

If flue pipe installation or air supply is an issue, the optional ETL certified outdoor enclosure is an ideal choice.



System Overview



Maintenance

4 Easy Steps!

1 Disconnect the drain water connection

2 Disengage the band clamp

3 Lower the evaporation chamber

4 Remove chamber for scale cleaning




Options

Steam Distribution Systems



Multi-Steam™ SD

For absorption distance of less than 3' (900mm)



Multi-Steam™ HD

High efficiency steam distributor (channel and header) with steam ejector eyelets



S.A.M.E2

For absorption distance of less than 5' (1500mm)

Outdoor Enclosure

- Hinged doors provide full access (serviceability) from the front, back and top of unit
- Fully insulated and constructed from heavy duty steel
- Stainless steel bottom drip pan
- Zinc primer and polyurethane powder coating for resistance against scratches and corrosion
- Built-in anti-freeze and overheat protection
- Easy installation on a roof curb, stand or slab
- Connection can be made from side or through the roof curb



Modular Design

Flexible Solution for Indoor/Outdoor Applications

Modular design offers flexibility and convenience; each module adds up to 210lbs/hr (100kg/hr) of steam capacity. With the smallest footprint in the industry, the SKG4 module can be easily installed and assembled on site when access is limited. Module assembly can be arranged in line, in an L shape, or back to back to accommodate any specific space conditions. Feed water, gas, water drain and flue connections can be located on either side of the enclosure.



Specifications

Output and Power Consumption

Model	No. of Modules	Steam Capacity (lb/hr) [kg/hr]	Input Capacity (btu/hr)[kW]	Current at 120Vac (A)	Current at 230Vac (A)	No. of Outlets	Multi-Steam header diam. in [mm]
SKG4-N1101	1	110 [50]	165,000 [49]	11	6	1	3" [76]
SKG4-N1551	1	155 [70]	215,000 [63]	11	6	1	3" [76]
SKG4-N1801	1	180 [80]	240,000 [70]	11	6	1	3" [76]
SKG4-N2101	1	210 [95]	249,000 [73]	11	6	1	3" [76]
SKG4-N2652	2	265 [120]	380,000 [112]	17	9	2	4" [100]
SKG4-N3102	2	310 [140]	430,000 [126]	17	9	2	4" [100]
SKG4-N3502	2	350 [160]	464,000 [136]	17	9	2	4" [100]
SKG4-N4052	2	405 [185]	498,000 [146]	17	9	2	4" [100]
SKG4-N5053	3	505 [230]	704,000 [206]	23	12	3	5" [125]
SKG4-N5603	3	560 [255]	713,000 [209]	23	12	3	5" [125]
SKG4-N6103	3	610 [275]	747,000 [219]	23	12	3	5" [125]
SKG4-N7104	4	710 [320]	953,000 [279]	29	15	4	(2x) 4" [100]
SKG4-N7654	4	765 [345]	962,000 [282]	29	15	4	(2x) 4" [100]
SKG4-N8104	4	810 [370]	996,000 [292]	29	15	4	(2x) 4" [100]

Integrated, Multi-Platform Controller

The SK4 Controller is configured specifically for your SKG4 Humidifier.

- User-friendly interface consisting of a menu driven 128 x 64 LCD with 8 function buttons for faster configuration and operation
- User rights management allows for menu to display only functions available to the category of user logged in
- Quick Config menu allows for faster and easier installation, by displaying only the most commonly used functions and configurations
- Independent scheduling system for unit operation and drain cycle, configurable via the menu or the BACnet communication interface
- In-field firmware upgradeable via SD card, USB or BACnet
- Simple viewing and exporting of trending log and alarm log

Optional features

- The selectable BACnet MS/TP or Modbus menus allow access to over 75 objects/ registers for integration with a BMS and IoT (Internet of Things)
- Ethernet module
- BACnet IP or Modbus IP
- Web services make it possible to perform humidifier configurations, remote diagnostics and many more functions from any location



Specify your SKG4 online

Humidifier System Design and Specification Web Application

Ready to specify your Humidifier? Neptronic has developed a web application that saves you time when sizing and specifying Neptronic commercial, industrial or residential humidifiers.



Features

- Automatic humidification load calculation
- Web based
- Selection specific report generator
- Only options related to your selections appear
- Manage users, clients, job sites and humidifier specs
- History log



Project	Humidifier	Dispersion	Options	Reports	Pricing
Type ☒ Isothermal (Hot Steam) ☐ Adiabatic (cold mist)					
Category ☐ Commercial Electric SKE ☒ Commercial Gas ☐ Residential Electric ☐ Commercial Electric SKE4 ☐ Steam to Steam ☐ Direct Steam					
Entering Air Conditions Temperature 15.6 °C Relative Humidity 35 %		Indoor Conditions Temperature 21.1 °C Relative Humidity 40 %		Distribution ☒ In Duct ☐ In Space	
Ventilation System ☐ Natural ☒ Mechanical ☐ Economizer Total Air Flow 5663 m ³ /hr Outside Air 100 %					
Humidifier(s) ☒ Enter Load Manually Entered Load 2.04 kg/hr Total Capacity 50.00 kg/hr Select Model					

Easy to Use

Go to neptronic.com, select Humidisoft and log in. Enter design requirements and Humidisoft automatically calculates the humidification load and adjusts available options based on your selections. When done, print a complete schedule, CSI and/or submittal report at the click of a button.

Projects	Humidifier	Dispersion	Options	Reports	Pricing
Flexible Steam Hose 1 3/8" 6 ft ☐ Straight Hump Silicone Hose SF 4501-35					
Drain Cooler ☒ IDC Internal Drain Cooler (standard feature) ☐ External Drain Cooler (thermostatic valve)					
Other Options ☒ BACnet (MS/TP) Network Capability ☐ Humidifier Weather Enclosure (W)					

Humidifier Product Line

SKE4 ⚡



Electric

- Capacities from 6 - 300 lbs/hr (2.7 - 134 kg/hr)
- Remove chamber easily, without tools
- Outdoor unit available

SKG4 🔥



Gas Fired

- Capacities from 110 - 810 lbs/hr (50 - 370kg/hr)
- Modular design
- Outdoor unit available

SKS4 ⬆️⬆️⬆️



Steam to Steam

- Capacities from 17 - 1250 lbs/hr (8 - 570 kg/hr)
- Scale management system for easy maintenance
- Insulated external panels

SKVF ➡️❄️❄️❄️



Evaporative Cooler

- Airflow up to 6000 CFM (10 194 m³)
- ECM fan with variable output
- Compact, quiet and standalone

SKR ⚡



Residential

- Capacities from 4.5 - 12 lbs/hr (3 - 5 kg/hr)
- Permanent cleanable chamber
- Reliable siphon drain


SKH4 🕒



High Pressure Atomizer

- Capacities up to 2800 lbs/hr (1270 kg/hr)
- Up to 6 zones
- Installation in-duct or in-space

SKV ➡️❄️❄️❄️



Evaporative

- Free cooling up to 22°F (12 °C)
- Custom design to fit your application
- Hygienic operation with silver ion dosing system


SKD 🌫️🌫️🌫️



Direct Steam

- Capacities from 5 - 1650 lbs/hr (2 - 750 kg/hr)
- Jacketed ou Multi-Steam™ SD/HD
- Unique electronic steam controller
- Optional pressurized condensate return (PCR) system

Distribution



Steam Distribution

- Multi-Steam™ SD/HD distribution
- S.A.M. and S.A.M.E2 wands
- SDU (Space distribution unit)



MANUFACTURER OF

-  **HVAC CONTROLS**
-  **ELECTRIC ACTUATORS**
-  **ACTUATED VALVES**
-  **HUMIDIFIERS**
-  **ELECTRIC HEATERS**



neptronic.com