

Model	Nb of heat exc.	Output steam capacity lb/hr (kg/h) for supply steam pressure					Steam outlet Qty & Ø in (mm)
		5 PSI 34.5kPa	8 PSI 55.1kPa	10 PSI 68.9kPa	12 PSI 82.7kPa	15 PSI 103.4kPa	
<b>SKS-100-SLP</b>	1	33 (15)	53 (24)	67 (30)	80 (36)	100 (45)	(1x) 3" (76)
<b>SKS-130-SLP</b>	1	43 (19)	69 (31)	87 (39)	104 (47)	130 (59)	(1x) 3" (76)
<b>SKS-190-SLP</b>	1	63 (28)	101 (46)	127 (57)	152 (69)	190 (86)	(1x) 3" (76)
<b>SKS-290-SLP</b>	1	97 (44)	155 (70)	193 (87)	232 (105)	290 (132)	(1x) 4" (108)
<b>SKS-390-SLP</b>	1	130 (59)	208 (94)	260 (118)	312 (142)	390 (177)	(1x) 4" (108)
<b>SKS-500-SLP</b>	1	167 (76)	267 (121)	333 (151)	400 (182)	500 (230)	(1x) 5" (133)
<b>SKS-690-SLP</b>	1	230 (104)	368 (167)	460 (209)	552 (251)	690 (314)	(1x) 5" (133)
<b>SKS-950-SLP</b>	1	317 (144)	507 (230)	633 (287)	760 (345)	950 (432)	(2x) 4" (108)
<b>SKS-1250-SLP</b>	2	417 (189)	667 (303)	833 (378)	1000 (454)	1250 (568)	(2x) 5" (133)